

The groups of pigments and their CF values

Inorganic pigments and fillers

2.3 ± 30 % kg CO_{2,eq.}/kg product

Metal and effect pigments

8.1 ± 20 % kg CO_{2,eq.}/kg product

Organic pigments

Single stage synthesis

11 ± 30 % kg CO_{2,eq.}/kg product

Multi-stage synthesis

24 ± 10 % kg CO_{2,eq.}/kg product

Ceramic frits

0.4 ± 10 % kg CO_{2,eq.}/kg product

CO_{2,eq.} = CO₂ equivalents

The voice of the European colourant industry

Product Carbon Footprint

Eurocolour e.V.

Mainzer Landstraße 55

60329 Frankfurt am Main/Germany

Phone: +49 69 2556 1351

Telefax: +49 69 2556 1250

E-mail: contact@eurocolour.org

<https://eurocolour.org/>

Register No. of the EU Transparency register:

90219 263 4607-21



Status: May 2022



Our aim

The Product Carbon Footprint (PCF) totals the greenhouse gas emissions of a product in CO₂-equivalents during its life cycle. Starting from the exploitation (mining) of raw materials, through the production process and use phase to recycling and finally disposal.

The pigment and filler industry was looking for a practical approach to CF assessment for its products and for communication to downstream users.

Our route – “cradle to gate”

More than half of the elements of the periodic table are utilized by the pigment and filler industry for the fabrication of its products. This results in a large variety of raw materials, being of mineral or petrochemical origin.

Pigments and fillers can be found in nearly all products of our everyday life. Thus, we decided to determine the CF values of the products from cradle (raw materials) to gate. Our companies have calculated the greenhouse gas emissions (in CO₂ equivalents) in relation to the various production processes and thereby determined the respective CF values of products within the plant's boundaries.

Grouping – our solution

Our aim was to obtain valid results, which meet scientific standards, in a cost-efficient manner. Thus, we divided pigments and fillers into subgroups. The Eurocolour secretariat was provided with the CF values of certain products, according to these groups, by the company members.

Our Approach

It is important to mention that there are currently no standardized methods for determining the PCF values. During the calculations the availability of CF values for the starting materials turned out to be problematic. As far as CF values were accessible in databases, these were used. If the CF values of raw materials were not available, CF values of products with a comparable production process were employed (read across).

Formulation ingredients with concentrations lower than 3 % were discarded. If the sum of the minor ingredients added up to 10 % or more of the formulation, one minor ingredient was chosen as representative for the calculation.

The error margin is about ± 30 % which is mainly due to inaccuracies of the raw materials' CF values.

Evaluation of the pigment CFs

Pigments and fillers are always used in mixtures to achieve effects and adjust colours. Regarding the evaluation of the published CF values, the differences in colour strength and concentration in use of pigments and fillers need to be taken into account.

Don't forget

- PCF = greenhouse gas emissions throughout the product life cycle
- Pigments and fillers are usually processed at low concentrations
- The contribution of pigments and fillers to the CF value of a product is almost negligible in comparison to the product life cycle (cradle to grave)
- The CF of many products is mainly determined during the use phase

